






























3.1	<i>Rubber Hose</i>	345
3.2	<i>PVC Hose</i>	353
3.3	<i>Ducting Hose</i>	359
3.4	<i>Conduit</i>	365
3.5	<i>Metallic Hose Assembiles</i>	371
3.6	<i>Composite Hose Assembiles</i>	377
3.7	<i>Hygienic Hose & Couplings</i>	381
3.8	<i>Fire Hose & Couplings</i>	391
3.9	<i>Suction & Delivery Couplings</i>	395
3.10	<i>Cam & Groove Couplings</i>	407
3.11	<i>Tanker Truck Couplings</i>	415
3.12	<i>Brass and S.Steel Hose Couplings</i>	423
3.13	<i>Stainless Steel Pipe Couplings</i>	431
3.14	<i>Nylon Hose Couplings</i>	437
3.15	<i>Hose Clips & Clamps</i>	441

PRODUCT INDEX

The Inti Hose Group industrial hose range will cater for most common mediums and is designed to complement the hydraulic hose range.

	Series	Page		Series	Page		
	Air and Water Hose	IPNBL25	346		Chemical Suction and Delivery Hose	IPXL10	350
	Air Delivery Hose	IMIN10	346		Fuel Hose	TBE	350
	Anti-Static Air Hose	ITUR20	346		Fuel Hose	TBSE	350
	Air Delivery Hose	IAIR20	346		Marine Fuel Hose	TBDE	350
	Air Brake Hose	J1402	346		Car Heater Hose SAE 20R3 c (212)	ICAR	350
	Compressor Hose	ICOM20	347		Fuel Hose Dispenser	FHD	351
	Compressor Hose Assembly	COMP	347				
	Suction and Delivery Food Grade Hose	IGAM10	347		Swage Ferrule for Industrial and PVC Hose - Light Duty Steel	LDF	351
	Delivery Food Grade Hose	IDRI10	347		Swage Ferrule for Industrial and PVC Hose - Light Duty Brass	BR/LDF	351
	Welding Hose	IWNB-20	347		Swage Ferrule for Industrial and PVC Hose - Light Duty Aluminium	AL/LDF	351
	Twin Line Welding Hose	IWBI20	347		Swage Ferrule for Industrial and PVC Hose - Light Duty Stainless Steel	SS/LDF	352
	Propane Gas Hose	IPRO20	347		Propane Gas Hose EN559/BS3212	GS/IPRO20	352
	Steam Hose Red	IVIG17	348		Propane Gas Hose EN559/BS3212	WR/IPRO20	352
	Steam Hose Black	IVIG17B	348		Fuel Hose Stainless Steel Overbraided	SS/PVZA	352
	Water Suction and Delivery Hose	IBEV10	348		Fuel Hose Galvanised Steel Overbraided	GS PVZA	352
	Water Suction and Delivery Hose	IWSH10	348				
	Radiator Hose	IRAD	349				
	Silicone Radiator Hose	SIL	349				
	Silicone Radiator Hose	SIL90	349				
	Oil Delivery Hose	100R6	349				
	Oil Suction and Delivery Hose	100S4	350				

For Technical Data please see Section 9

Air and Water Hose - IPNBL25



Tube: Black, smooth SBR rubber.
Reinforcement: Synthetic textile yarns.
Cover: Blue, abrasion, ageing and weather resistant SBR/EPDM rubber.
Coil Lengths: 30 up to 100 metres.
Temperature Range: -20°C to + 70°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IPNBL25-006	1/4	6	14	362	25
IPNBL25-010	3/8	10	19	362	25
IPNBL25-013	1/2	13	24	362	25
IPNBL25-019	3/4	19	32	362	25
IPNBL25-025	1	25	39	362	25

Air Delivery Hose - BS EN ISO 2398/BS 5118/2 -IAIR20



Tube: Black, smooth synthetic rubber.
Reinforcement: Synthetic textile yarns.
Cover: Black, smooth SBR/EPDM rubber, resistant to abrasion, ageing and weathering.
Coil Lengths: 50 up to 100 metres.
Temperature Range: -20°C to + 80°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IAIR20-006	1/4	6.5	14	290	20
IAIR20-008	5/16	8	16	290	20
IAIR20-010	3/8	9.5	18	290	20
IAIR20-013	1/2	12.7	23	290	20
IAIR20-019	3/4	19	30	290	20
IAIR20-025	1	25	37	290	20

Air Delivery Hose - IMIN10



Tube: Black, oil, mist resistant smooth SBR rubber.
Reinforcement: Synthetic textile fabrics.
Cover: Black, abrasion, ageing and weather resistant SBR rubber.
Coil Lengths: 40 metres.
Temperature Range: -30°C to + 70°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IMIN10-032	1 1/4	32	42	145	10
IMIN10-038	1 1/2	38	48	145	10
IMIN10-050	2	50	60	145	10

Air Delivery Hose - SAE J1402-A



Tube: Black, smooth NBR rubber.
Reinforcement: Synthetic textile yarns.
Cover: Black, smooth, abrasion, ageing and weather-resistant CR rubber.
Coil Lengths: 50 metres.
Temperature Range: -40°C to + 93°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
J1402-04	1/4	6.3	15.9	145	10
J1402-05	5/16	7.9	17.5	145	10
J1402-06	3/8	9.5	19.5	145	10
J1402-08	1/2	12.7	22.2	145	10
J1402-10	5/8	15.9	27	145	10

Anti-Static Air Hose - BS EN ISO 2398/BS 5118/2 -ITUR20



Tube: Black, resistant to traces of oil mist, antistatic, smooth EPDM rubber.
Reinforcement: Synthetic textile yarns.
Cover: Black, abrasion and weather resistant, antistatic EPDM rubber.
Coil Lengths: 30 up to 100 metres.
Temperature Range: -30°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
ITUR20-010	3/8	10	19	290	20
ITUR20-013	1/2	13	23	290	20
ITUR20-019	3/4	19	30	290	20
ITUR20-025	1	25	37	290	20

Compressor Hose - BS EN ISO 2398/BS 5118/2 -ICOM20



Tube: Black, resistant to minimum oil traces, smooth SBR rubber.
Reinforcement: Synthetic textile fabrics.
Cover: Yellow, abrasion and weather resistant SBR rubber.
Coil Lengths: 20 up to 40 metres.
Temperature Range: -30°C to + 70°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
ICOM20-019	3/4	19	30	290	20
ICOM20-025	1	25	36	290	20
ICOM20-032	1 1/4	32	48	290	20
ICOM20-038	1 1/2	38	51	290	20
ICOM20-051	2	51	66	290	20

3-1

Compressor Hose Assembly - BS 5118/2 - COMP

Tube: Black, Rubber
Reinforcement: Synthetic textile fabrics.
Cover: Yellow, abrasion and weather resistant Rubl
Coil Lengths: 15 metres.
Temperature Range: -25°C to + 70°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
*COMP-05	3/4	19	30	290	20

*(Complete with safety clamps)



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
**COMP-06	3/4	19	30	232	16

** (Complete with crimped fittings)

Suction and Delivery Food Grade Hose - IGAM10

Tube: Rubber hose with smooth, white, food quality inner tube.
Reinforcement: Textile yarn and embedded metal spiral reinforcement.
Cover: Blue, abrasion, ageing and weather resistant.
Coil Lengths: 40 metres.
Temperature Range: -40°C to + 90°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IGAM10-025	1	25	37	145	10
IGAM10-032	1 1/4	32	44	145	10
IGAM10-038	1 1/2	38	50	145	10
IGAM10-050	2	51	65	145	10
IGAM10-063	2 1/2	63.5	77	145	10

Delivery Food Grade Hose - IDRI10

Tube: White colour, non-toxic, smooth synthetic rubber.
Reinforcement: Synthetic textile yarns.
Cover: Blue smooth, abrasion, and weather resistant synthetic rubber.
Coil Lengths: 30 up to 100 metres.
Temperature Range: -15°C to + 70°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IDRI10-010	3/8	10	19	145	10
IDRI10-013	1/2	13	23	145	10
IDRI10-016	5/8	16	26	145	10
IDRI10-019	3/4	19	31	145	10
IDRI10-025	1	25	39	145	10

Welding Hose EN559 - IWNB20 - Blue IWNR20 - Red

Tube: Black, smooth SBR rubber, resistant to welding gases. (Not suitable for LPG). Good resistance to ignition.
Reinforcement: Synthetic textile yarns.
Cover: Smooth, Blue or Red SBR/EPDM rubber, resistant to abrasion, ageing, hot surfaces and incandescent particles.
Coil Lengths: 30 up to 100 metres.
Temperature Range: -25°C to + 80°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IWNB20-006	1/4	6	12	290	20
IWNB20-010	3/8	10	17	290	20
IWNR20-006	1/4	6	12	290	20
IWNR20-010	3/8	10	17	290	20

Twin-Line Welding Hose EN559 - IWB120

Tube: Black, smooth SBR rubber, resistant to welding gases. (Not suitable for LPG). Good resistance to ignition.
Reinforcement: Synthetic textile yarns.
Cover: Dual Blue and Red smooth SBR/EPDM rubber, resistant to abrasion, ageing, hot surfaces and incandescent particles.
Coil Lengths: 30 up to 100 metres.
Temperature Range: -25°C to + 80°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IWB120-006	1/4	6	12	290	20
IWB120-010	3/8	10	17	290	20

Propane Gas Hose - EN559/BS3212 - IPRO20

Tube: Black, LPG-resistant, smooth NBR rubber.
Reinforcement: High strength polyester yarn 2 ply.
Cover: Weather abrasion ozone and flame resistant, orange compound.
Coil Lengths: 30 up to 100 metres.
Temperature Range: -35°C to + 80°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IPRO20-005	3/16	5	12	290	20
IPRO20-006	1/4	6.3	13.3	290	20
IPRO20-008	5/16	8	15	290	20
IPRO20-010	3/8	10	17	290	20
IPRO20-013	1/2	12.5	21	290	20

Steam Hose Red
- **IVIG17**



Tube: Black inner made of heat resistant compounds.
Reinforcement: Metal reinforcement and micro pin pricked.
Cover: Red cloth impression, ageing and weather resistant rubber cover.
Coil Lengths: Up to 61 metres.
Temperature Range: -40°C to + 210°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IVIG17-013	1/2	13	25	250	17
IVIG17-019	3/4	19	32	250	17
IVIG17-025	1	25	38	250	17
IVIG17-038	1 1/2	38	54	250	17

Steam Hose Black
- **IVIG17B**



Tube: Black inner made of heat resistant compounds.
Reinforcement: Metal reinforcement and micro pin pricked.
Cover: Black cloth impression, ageing and weather resistant rubber cover.
Coil Lengths: Up to 61 metres.
Temperature Range: -40°C to + 210°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IVIG17B-013	1/2	13	25	250	17
IVIG17B-019	3/4	19	32	250	17
IVIG17B-025	1	25	38	250	17
IVIG17B-038	1 1/2	38	54	250	17

Water Suction and Delivery Hose
- **IBEV10**



Tube: Black, smooth SBR rubber.
Reinforcement: Synthetic textile fabrics and embedded steel wire helix.
Cover: Black, abrasion, ageing and weather resistant SBR rubber.
Coil Lengths: 61 metres.
Temperature Range: -40°C to +90°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IBEV10-025	1	25	35	145	10
IBEV10-032	1 1/4	32	42	145	10
IBEV10-038	1 1/2	38	49	145	10
IBEV10-050	2	51	62	145	10
IBEV10-063	2 1/2	63.5	76	145	10

Water Suction and Delivery Hose
- **IWSH10**



Tube: Black, smooth EPDM rubber.
Reinforcement: Spiral high tensile cords and four steel helix wires.
Cover: Black weather resistant EPDM rubber.
Coil Lengths: 61 metres.
Temperature Range: -22°C to +90°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IWSH10-019	3/4	19	29	150	10
IWSH10-025	1	25	35	150	10
IWSH10-032	1 1/4	32	42	150	10
IWSH10-038	1 1/2	38	49	150	10
IWSH10-051	2	51	63	150	10
IWSH10-063	2 1/2	63	76	150	10
IWSH10-076	3	76	89	150	10
IWSH10-102	4	102	118	150	10
IWSH10-127	5	127	145	150	10
IWSH10-152	6	152	174	150	10
IWSH10-203	8	203	228	150	10

3-1

Radiator Hose - IRAD

Tube: Black, heat resistant EPDM rubber.
Reinforcement: Synthetic textile fabric with steel wire helix embedded between the layers.
Cover: Black, heat, weather, ozone resistant EPDM rubber.
Coil Lengths: 1 metre.
Temperature Range: -40°C to + 120°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IRAD-14	7/8	22	30	145	10
IRAD-16	1	25	34	145	10
IRAD-18	1 1/8	28	36	145	10
IRAD-20	1 1/4	32	41	145	10
IRAD-22	1 3/8	35	45	145	10
IRAD-24	1 1/2	38	47	145	10
IRAD-28	1 3/4	44.5	55	145	10
IRAD-32	2	51	61	145	10

Silicone Radiator Hose - SIL

Tube: Blue silicone tube resistant to trace oil mist and anti freeze solutions.
Reinforcement: Three ply synthetic textile reinforcements.
Cover: Blue silicone tube resistant to abrasion, aging, weathering, oil mist and anti freeze solutions.
Coil Lengths: 1 metre.
Temperature Range: -50°C to + 235°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
SIL-006	1/4	6	14	25	2
SIL-008	5/16	8	16	25	2
SIL-010	3/8	10	18	25	2
SIL-013	1/2	13	21	25	2
SIL-016	5/8	16	24	25	2
SIL-019	3/4	19	27	25	2
SIL-022	7/8	22	30	25	2
SIL-025	1	25	34	25	2
SIL-028	1 1/8	28	37	25	2
SIL-032	1 1/4	32	41	25	2
SIL-035	1 3/8	35	44	25	2
SIL-038	1 1/2	38	47	25	2
SIL-042	1 5/8	42	50	25	2
SIL-045	1 3/4	45	54	25	2
SIL-048	1 7/8	48	57	25	2
SIL-051	2	51	60	25	2
SIL-054	2 1/8	54	63	25	2
SIL-057	2 1/4	57	67	25	2
SIL-061	2 3/8	61	71	25	2
SIL-063	2 1/2	63	73	25	2
SIL-070	2 3/4	70	80	25	2
SIL-076	3	76	86	25	2
SIL-080	3 1/8	80	90	25	2
SIL-090	3 1/2	90	100	25	2
SIL-102	4	102	112	25	2

Silicone Radiator Hose - SIL 90

Tube: Blue silicone tube resistant to trace oil mist and anti freeze solutions.
Reinforcement: Three ply synthetic textile reinforcements.
Cover: Blue silicone tube resistant to abrasion, aging, weathering, oil mist and anti freeze solutions.
Leg Length: 102 mm.
Temperature Range: -50°C to + 235°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
SIL90-006	1/4	6	14	25	2
SIL90-008	5/16	8	16	25	2
SIL90-010	3/8	10	18	25	2
SIL90-013	1/2	13	21	25	2
SIL90-016	5/8	16	24	25	2
SIL90-019	3/4	19	27	25	2
SIL90-022	7/8	22	30	25	2
SIL90-025	1	25	34	25	2
SIL90-028	1 1/8	28	37	25	2
SIL90-032	1 1/4	32	41	25	2
SIL90-035	1 3/8	35	44	25	2
SIL90-038	1 1/2	38	47	25	2
SIL90-042	1 5/8	42	50	25	2
SIL90-045	1 3/4	45	54	25	2
SIL90-048	1 7/8	48	57	25	2
SIL90-051	2	51	60	25	2
SIL90-054	2 1/8	54	63	25	2
SIL90-057	2 1/4	57	67	25	2
SIL90-061	2 3/8	61	71	25	2
SIL90-063	2 1/2	63	73	25	2
SIL90-070	2 3/4	70	80	25	2
SIL90-076	3	76	86	25	2
SIL90-080	3 1/8	80	90	25	2
SIL90-090	3 1/2	90	100	25	2
SIL90-102	4	102	112	25	2

Oil Delivery Hose - EN 854 - 100R6

Tube: Black, oil resistant NBR rubber.
Reinforcement: Synthetic textile fabrics.
Cover: Black, oil and ozone resistant CR rubber.
Coil Lengths: Up to 50 metres.
Temperature Range: -40°C to + 100°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
100R6-03	3/16	4.8	11.1	493	34
100R6-04	1/4	6.4	12.7	406	28
100R6-05	5/16	7.9	14.3	406	28
100R6-06	3/8	9.5	15.9	406	28
100R6-08	1/2	12.7	19.8	406	28
100R6-10	5/8	16	23	348	24
100R6-12	3/4	19	27	304	21
100R6-16	1	25	35	290	20

Oil Suction and Delivery Hose - 100S4



Tube: Black, smooth NBR rubber.
Reinforcement: Textile yarn and embedded metal spiral reinforcement, copper wire to ensure the electric conductivity, antistatic smooth, cloth impression.
Cover: Black, oil, abrasion and weathering resistant rubber.
Coil Lengths: 61 metres.
Temperature Range: -40°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
100S4-12	3/4	19	29	145	10
100S4-16	1	25	35	145	10
100S4-20	1 1/4	32	43	145	10
100S4-24	1 1/2	38	50	145	10
100S4-28	1 25/32	45	57	145	10
100S4-32	2	51	63	145	10
100S4-36	2 1/4	57	68	145	10
100S4-38	2 3/8	60	73	145	10
100S4-40	2 1/2	63.5	77	145	10
100S4-48	3	76	90	145	10
100S4-64	4	102	119	145	10

Chemical Suction and Delivery Hose - IPXL10



Tube: Smooth transparent UHMWPE conductive tube.
Reinforcement: Synthetic textile fabrics and embedded steel wire helix.
Cover: Green, cloth impression, abrasion, ozone and weathering resistant rubber.
Coil Lengths: 40 metres.
Temperature Range: -30°C to + 80°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
IPXL10-025	1	25	39	145	10
IPXL10-032	1 1/4	32	46	145	10
IPXL10-038	1 1/2	38	52	145	10
IPXL10-051	2	51	66	145	10

Fuel Hose BS AU 108 C4/L4/R - TBE



Tube: Black smooth rubber suitable for use with diesel, petrol and unleaded fuels.
Reinforcement: Synthetic textile fabric braid.
Cover: Black abrasion resistant rubber bonded with a textile fabric cover.
Coil Lengths: 15 metres.
Temperature Range: -30°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
TBE-003	1/8	3	7	120	8
TBE-004	5/32	4	9	120	8
TBE-005	3/16	5	11	120	8
TBE-006	1/4	6	13	120	8
TBE-008	5/16	8	14.5	120	8

Fuel Hose BS AU 108 C4/L4/R - TBSE



Tube: Black smooth rubber suitable for use with diesel, petrol and unleaded fuels.
Reinforcement: Synthetic textile fabric braid.
Cover: Black smooth abrasion resistant rubber.
Coil Lengths: 15 metres.
Temperature Range: -30°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
TBSE-003	1/8	3	7	120	8
TBSE-004	5/32	4	9	120	8
TBSE-005	3/16	5	10	120	8
TBSE-006	1/4	6	13	120	8
TBSE-008	5/16	8	16	120	8
TBSE-010	3/8	10	18	120	8
TBSE-012	1/2	12	23	120	8
TBSE-019	3/4	19	29	120	8
TBSE-025	1	25	36	120	8

Marine Fuel Hose ISO 7840 Type A - TBDE



Tube: Black smooth rubber suitable for use with diesel, petrol and unleaded fuels.
Reinforcement: Synthetic textile fabric braid.
Cover: Black smooth abrasion resistant rubber.
Temperature Range: -30°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure		Coil Lengths (m)
	ins	mm		PSI	Bar	
TBDE-006	1/4	6	16	50	3.4	100
TBDE-008	5/16	8	18	50	3.4	100
TBDE-010	3/8	10	20	50	3.4	100
TBDE-013	1/2	12	23	50	3.4	100
TBDE-016	5/8	16	26.5	50	3.4	100
TBDE-019	3/4	19	30	50	3.4	100
TBDE-025	1	25	36	50	3.4	40
TBDE-032	1 1/4	32	43	50	3.4	40
TBDE-038	1 1/2	38	49	50	3.4	40
TBDE-051	2	51	62	50	3.4	40

Car Heater Hose SAE 20R3c (212) - ICAR



Tube: Black smooth EPDM rubber resistant to glycol based anti-freeze solutions.
Reinforcement: Polyester cord reinforcement.
Cover: Black smooth abrasion resistant rubber.
Temperature Range: -30°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure		Coil Lengths (m)
	ins	mm		PSI	Bar	
ICAR-010	3/8	10	20	130	9	100
ICAR-012	1/2	12	21	130	9	100
ICAR-016	5/8	16	25	130	9	100
ICAR-019	3/4	19	29	130	9	50
ICAR-025	1	25	33	130	9	50

RUBBER HOSE

Fuel Hose Dispenser



Part Number

FHD-01

Swage Ferrule for Industrial - PVC Hose Light Duty Brass



Part Number	I.D. (mm)	O.D. (mm)	Hole Diameter
BR/LDF-06-12	12	14	6
BR/LDF-06-13	13	15	6
BR/LDF-06-15	15	17	6
BR/LDF-08-15	15	17	8
BR/LDF-10-17	17	19	10
BR/LDF-12-18	18	20	12
BR/LDF-12-20	20	22	12
BR/LDF-15-23	23	25	15
BR/LDF-15-25	25	27	15
BR/LDF-18-28	28	30	18
BR/LDF-20-30	30	32	20
BR/LDF-20-33	33	35	20
BR/LDF-25-36	36	38	25
BR/LDF-25-40	40	42	25

3.
1

Swage Ferrule for Industrial and PVC Hose - Light Duty Steel



Part Number	I.D. (mm)	O.D. (mm)	Hole Diameter
LDF-06-12	12	14	6
LDF-06-13	13	15	6
LDF-06-15	15	17	6
LDF-08-15	15	17	8
LDF-10-17	17	19	10
LDF-12-18	18	20	12
LDF-12-20	20	22	12
LDF-15-23	23	25	15
LDF-15-25	25	27	15
LDF-18-28	28	30	18
LDF-20-30	30	32	20
LDF-20-33	33	35	20
LDF-25-36	36	38	25
LDF-25-40	40	42	25
LDF-36-46	46	50	36
LDF-40-57	57	60	40
LDF-52-67	67	70	52
LDF-63-76	76	80	63
LDF-71-86	86	90	71

Swage Ferrule for Industrial - PVC Hose Light Duty Aluminium



Part Number	I.D. (mm)	O.D. (mm)	Hole Diameter
AL/LDF-06-12	12	14	6
AL/LDF-06-13	13	15	6
AL/LDF-06-15	15	17	6
AL/LDF-08-15	15	17	8
AL/LDF-10-17	17	19	10
AL/LDF-12-18	18	20	12
AL/LDF-12-20	20	22	12
AL/LDF-15-23	23	25	15
AL/LDF-15-25	25	27	15
AL/LDF-18-28	28	30	18
AL/LDF-20-30	30	32	20
AL/LDF-20-33	33	35	20
AL/LDF-25-36	36	38	25
AL/LDF-25-40	40	42	25
AL/LDF-36-46	46	50	36
AL/LDF-40-57	57	60	40
AL/LDF-52-67	67	70	52
AL/LDF-63-76	76	80	63
AL/LDF-71-86	86	90	71

Swage Ferrule for Industrial and PVC Hose - Light Duty Stainless Steel



Part Number	I.D. mm	O.D. mm	Hole Diameter
SS/LDF-06-12	12	14	6
SS/LDF-06-13	13	15	6
SS/LDF-06-15	15	17	6
SS/LDF-08-15	15	17	8
SS/LDF-10-17	17	19	10
SS/LDF-12-18	18	20	12
SS/LDF-12-20	20	22	12
SS/LDF-15-23	23	25	15
SS/LDF-15-25	25	27	15
SS/LDF-18-28	28	30	18
SS/LDF-20-30	30	32	20
SS/LDF-20-33	33	35	20
SS/LDF-25-36	36	38	25
SS/LDF-25-40	40	42	25

Propane Gas Hose EN559/BS3212 - GS/IPR020



Tube: Black LPG-resistant smooth NBR rubber
Reinforcement: High strength polyester 2 ply yarn
Cover: Galvanised Steel overbraided weather, abrasion ozone and flame resistant orange compound
Coil Lengths: 30 up to 100 metres.
Temperature Range: -35°C to +80°C

Part Number	ins	Bore Size mm	O.D. (mm)	Working Pressure PS	Working Pressure Bar
GS/IPR020-006	1/4	6.3	13.3	290	20
GS/IPR020-008	5/16	8.0	15.0	290	20
GS/IPR020-010	3/8	10.0	17.0	290	20

Propane Gas Hose EN559/BS 3212 - WR/IPR020



Tube: Black LPG resistant smooth NBR rubber
Reinforcement: Steel Braided wire
Cover: Weather, abrasion ozone and flame resistant orange compound
Coil Lengths: 30 up to 100 metres.
Temperature Range:

Part Number	ins	Bore Size mm	O.D. mm	Working Pressure PSI	Working Pressure Bar
WR/IPR020-006	1/4	6.3	14.0	290	20
WR/IPR020-008	5/16	8.0	16.0	290	20
WR/IPR020-010	3/8	10.0	18.0	290	20
WR/IPR020-012	1/2	12.5	21.0	290	20

Fuel Hose Stainless Steel Overbraided - SS/PVZA



Tube: Nitrile Rubber
Reinforcement: Unreinforced
Cover: 304 Stainless Steel Overbraid
Coil Lengths: 50 metres
Temperature Range: -20°C to +80°C

Part Number	Size	Bore Size ins	Bore Size mm	O.D. mm	Working Pressure PSI	Working Pressure Bar
SS/PVZA-006	04	1/4	6.0	10.0	217	15
SS/PVZA-008	05	5/16	8.0	12.0	217	15
SS/PVZA-010	06	3/8	10.0	14.0	217	15
SS/PVZA-012	08	1/2	12.0	17.0	217	15
SS/PVZA-016	10	5/8	16.0	22.0	217	15
SS/PVZA-019	12	3/4	19.0	27.0	145	10
SS/PVZA-025	16	1	26.0	34.0	145	10
SS/PVZA-032	20	1 1/4	32.0	44.0	145	10
SS/PVZA-038	24	1 1/2	38.0	54.0	87	6
SS/PVZA-050	32	2	50.0	64.0	87	6

Fuel Hose Galvanised Steel Overbraided - GSPVZA



Tube: Nitrile Rubber
Reinforcement: Unreinforced
Cover: Galvanised Steel Overbraid
Coil Lengths: 50 metres
Temperature Range: -20°C to +80°C

Part Number	Size	Bore Size ins	Bore Size mm	O.D. mm	Working Pressure PSI	Working Pressure Bar
GS/PVZA-006	04	1/4	6.0	10.0	217	15
GS/PVZA-008	05	5/16	8.0	13.0	217	15
GS/PVZA-010	06	3/8	10.0	15.0	217	15
GS/PVZA-012	08	1/2	12.0	19.0	217	15
GS/PVZA-016	10	5/8	16.0	21.0	217	15
GS/PVZA-019	12	3/4	19.0	25.0	145	10
GS/PVZA-025	16	1	25.0	32.0	145	10
GS/PVZA-032	20	1 1/4	32.0	44.0	145	10
GS/PVZA-038	24	1 1/2	38.0	54.0	87	6
GS/PVZA-050	32	2	50.0	64.0	87	6