






PRODUCT INDEX

	Series	Page
 Metric Polyurethane Tube Black/Blue/Red/White/Green/Yellow	MPT	472
 Imperial Nylon Tube Black/White/Blue/Red/Green/Yellow	INT	473
 Metric Nylon Tube Black/White/Blue/Red/Green/Yellow	MNT	474
 Air Brake Coils - Suzy Red / Yellow	SUZY	475
 Polyurethane Recoil Hose Assemblies	RHC	475

Black Metric Polyurethane Tube - MPTN



Tube: Polyurethane
Reinforcement: Unreinforced
Cover: Black
Coil Lengths: 25 metres
Temperature Range: -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
MPTN-004	2.5	4	190	13
MPTN-005	3	5	160	11
MPTN-006	4	6	155	10.5
MPTN-008	5	8	150	10
MPTN-010	6.5	10	125	8.5
MPTN-012	8	12	120	8

White Metric Polyurethane Tube - MPTW



Tube: Polyurethane
Reinforcement: Unreinforced
Cover: White
Coil Lengths: 25 metres
Temperature Range: -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
MPTW-004	2.5	4	190	13
MPTW-005	3	5	160	11
MPTW-006	4	6	155	10.5
MPTW-008	5	8	150	10
MPTW-010	6.5	10	125	8.5
MPTW-012	8	12	120	8

4.
2

Blue Metric Polyurethane Tube - MPTB



Tube: Polyurethane
Reinforcement: Unreinforced
Cover: Blue
Coil Lengths: 25 metres
Temperature Range: -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
MPTB-004	2.5	4	190	13
MPTB-005	3	5	160	11
MPTB-006	4	6	155	10.5
MPTB-008	5	8	150	10
MPTB-010	6.5	10	125	8.5
MPTB-012	8	12	120	8

Green Metric Polyurethane Tube - MPTG



Tube: Polyurethane
Reinforcement: Unreinforced
Cover: Green
Coil Lengths: 25 metres
Temperature Range: -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
MPTG-004	2.5	4	190	13
MPTG-005	3	5	160	11
MPTG-006	4	6	155	10.5
MPTG-008	5	8	150	10
MPTG-010	6.5	10	125	8.5
MPTG-012	8	12	120	8

Red Metric Polyurethane Tube - MPTR



Tube: Polyurethane
Reinforcement: Unreinforced
Cover: Red
Coil Lengths: 25 metres
Temperature Range: -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
MPTR-004	2.5	4	190	13
MPTR-005	3	5	160	11
MPTR-006	4	6	155	10.5
MPTR-008	5	8	150	10
MPTR-010	6.5	10	125	8.5
MPTR-012	8	12	120	8

Yellow Metric Polyurethane Tube - MPTY



Tube: Polyurethane
Reinforcement: Unreinforced
Cover: Yellow
Coil Lengths: 25 metres
Temperature Range: -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
MPTY-004	2.5	4	190	13
MPTY-005	3	5	160	11
MPTY-006	4	6	155	10.5
MPTY-008	5	8	150	10
MPTY-010	6.5	10	125	8.5
MPTY-012	8	12	120	8

FLEXIBLE TUBE

Black Imperial Nylon Tube - BS5409 - INTN

Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: Black
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
INTN-02	02	0.075	1/8	300	20
INTN-03	03	0.117	3/16	300	20
INTN-04	04	0.170	1/4	300	20
INTN-05	05	0.212	5/16	250	17
INTN-06	06	0.250	3/8	250	17
INTN-08	08	0.375	1/2	250	17

Red Imperial Nylon Tube - BS5409 - INTR

Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: Red
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
INTR-04	04	0.170	1/4	300	20
INTR-05	05	0.212	5/16	250	17
INTR-06	06	0.250	3/8	250	17
INTR-08	08	0.375	1/2	250	17

White Imperial Nylon Tube - BS5409 - INTW

Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: White
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
INTW-02	02	0.075	1/8	300	20
INTW-03	03	0.117	3/16	300	20
INTW-04	04	0.170	1/4	300	20
INTW-05	05	0.212	5/16	250	17
INTW-06	06	0.250	3/8	250	17
INTW-08	08	0.375	1/2	250	17
INTW-10	10	0.500	5/8	200	14
INTW-12	12	0.594	3/4	200	14
INTW-16	16	0.813	1	180	12

Green Imperial Nylon Tube - BS5409 - INTG

Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: Green
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
INTG-04	04	0.170	1/4	300	20
INTG-05	05	0.212	5/16	250	17
INTG-06	06	0.250	3/8	250	17
INTG-08	08	0.375	1/2	250	17

Blue Imperial Nylon Tube - BS5409 - INTB

Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: Blue
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
INTB-04	04	0.170	1/4	300	20
INTB-05	05	0.212	5/16	250	17
INTB-06	06	0.250	3/8	250	17
INTB-08	08	0.375	1/2	250	17

Yellow Imperial Nylon Tube - BS6509 - INTY

Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: Yellow
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
INTY-04	04	0.170	1/4	300	20
INTY-05	05	0.212	5/16	250	17
INTY-06	06	0.250	3/8	250	17
INTY-08	08	0.375	1/2	250	17

4.
2

White Metric Nylon Tube - BS 5409 - MNTW



Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: White
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
MNTW-004	2.5	4	580	40
MNTW-005	3	5	580	40
MNTW-006	4	6	580	40
MNTW-008	6	8	580	40
MNTW-010	8	10	580	40
MNTW-012	9	12	580	40

Red Metric Nylon Tube - BS 5409 - MNTR



Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: Red
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
MNTR-004	2.5	4	580	40
MNTR-006	4	6	580	40
MNTR-008	6	8	580	40
MNTR-010	8	10	580	40
MNTR-012	9	12	580	40

4.
2

Black Metric Nylon Tube - BS 5409 - MNTN



Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: Black
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
MNTN-004	2.5	4	580	40
MNTN-005	3	5	580	40
MNTN-006	4	6	580	40
MNTN-008	6	8	580	40
MNTN-010	8	10	580	40
MNTN-012	9	12	580	40

Green Metric Nylon Tube - BS 5409 - MNTG



Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: Green
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
MNTG-004	2.5	4	580	40
MNTG-006	4	6	580	40
MNTG-008	6	8	580	40
MNTG-010	8	10	580	40
MNTG-012	9	12	580	40

Blue Metric Nylon Tube - BS 5409 - MNTB



Tube: Nylon Type 12
Reinforcement: Unreinforced
Cover: Blue
Coil Lengths: 30 metres
Temperature Range: -20°C to +100°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
MNTB-004	2.5	4	580	40
MNTB-006	4	6	580	40
MNTB-008	6	8	580	40
MNTB-010	8	10	580	40
MNTB-012	9	12	580	40

Yellow Metric Nylon Tube - BS 5409 - MNTY



Tube: Polyurethane
Reinforcement: Unreinforced
Cover: Yellow
Coil Lengths: 25 metres
Temperature Range: -20°C to +75°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
MNTY-004	2.5	4	580	40
MNTY-006	4	6	580	40
MNTY-008	6	8	580	40
MNTY-010	8	10	580	40
MNTY-012	9	12	580	40

Air Brake Coils - Suzy Red



Part Number	I.D. mm	O.D. (mm)
SUZY RED	9	12

Air Brake Coils - Suzy Yellow



Part Number	I.D. mm	O.D. (mm)
SUZY YELLOW	9	12

Polyurethane Recoil Hose Assemblies - RHC

These assemblies have low resistance to extension forces so worker fatigue is substantially reduced. Applications cover most pneumatic and other uses that have requirements from -40°F to +180°F (-40°C to +82°C) and a nominal working pressure of 100 psi @ +75°F (24°C).

Features

- Kink Resistance
- Wear Resistant
- Light weight and mobile
- Straight BSPT swivel male ends
- Stretches full length
- Low working fatigue
- Excellent oxidation, chemical, hydrolysis and ozone resistance



4.
2

Part Number	ID (mm)	O.D. (mm)	Working length mtrs	Coil ID (mm)	Colour	Swivel BSPT male ends
RHC-08-2MY	5	8	2.5	25	Yellow	1/4
RHC-08-4MY	5	8	4	25	Yellow	1/4
RHC-08-7MY	5	8	7.5	25	Yellow	1/4
RHC-10-2MY	6.5	10	2.5	30	Yellow	1/4
RHC-10-5MY	6.5	10	5	30	Yellow	1/4
RHC-10-7MY	6.5	10	7.5	30	Yellow	1/4
RHC-12-2MY	8	12	2.5	40	Yellow	3/8
RHC-12-5MY	8	12	5	40	Yellow	3/8
RHC-12-7MY	8	12	7.5	40	Yellow	3/8
RHC-16-2MY	11	16	2.5	70	Yellow	1/2
RHC-16-5MY	11	16	5	70	Yellow	1/2
RHC-16-7MY	11	16	7.5	70	Yellow	1/2
RHC-08-2MB	5	8	2.5	25	Blue	1/4
RHC-08-4MB	5	8	4	25	Blue	1/4
RHC-08-7MB	5	8	7.5	25	Blue	1/4
RHC-10-2MB	6.5	10	2.5	30	Blue	1/4
RHC-10-5MB	6.5	10	5	30	Blue	1/4
RHC-10-7MB	6.5	10	7.5	30	Blue	1/4
RHC-12-2MB	8	12	2.5	40	Blue	3/8
RHC-12-5MB	8	12	5	40	Blue	3/8
RHC-12-7MB	8	12	7.5	40	Blue	3/8
RHC-16-2MB	11	16	2.5	70	Blue	1/2
RHC-16-5MB	11	16	5	70	Blue	1/2
RHC-16-7MB	11	16	7.5	70	Blue	1/2
RHC-08-2MR	5	8	2.5	25	Red	1/4
RHC-08-4MR	5	8	4	25	Red	1/4
RHC-08-7MR	5	8	7.5	25	Red	1/4
RHC-10-2MR	6.5	10	2.5	30	Red	1/4
RHC-10-5MR	6.5	10	5	30	Red	1/4
RHC-10-7MR	6.5	10	7.5	30	Red	1/4
RHC-12-2MR	8	12	2.5	40	Red	3/8
RHC-12-5MR	8	12	5	40	Red	3/8
RHC-12-7MR	8	12	7.5	40	Red	3/8
RHC-16-2MR	11	16	2.5	70	Red	1/2
RHC-16-5MR	11	16	5	70	Red	1/2
RHC-16-7MR	11	16	7.5	70	Red	1/2